

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **03-262523**
 (43)Date of publication of application : **22.11.1991**

(51)Int.Cl. **B01D 71/70**
C01B 13/02
// B01D 71/44

(21)Application number :	02-060114	(71)Applicant :	SHIN ETSU POLYMER CO LTD
(22)Date of filing :	13.03.1990	(72)Inventor :	NAKAMURA AKIO OGINO TSUTOMU HAYASHI OSAMI

(54) OXYGEN ENRICHING COMPOSITE MEMBRANE

(57)Abstract:

PURPOSE: To obtain a thin oxygen enriching membrane excellent in oxygen permeability and oxygen separating capacity by adding high silica zeolite to a polyorganosiloxane.

CONSTITUTION: A polymer membrane having an oxygen/nitrogen separation factor of 1.8 or more, an oxygen transmission coefficient of $1 \times 10^{-10} \text{ cm}^3 \cdot \text{cm} / \text{cm}^2 \cdot \text{sec} \cdot \text{cmHg}$ or more and a thickness of 0.01-10 μm is formed to at least the single surface of a polyorganosiloxane membrane containing high silica zeolite (commercial 'Silicalite' is pref.). It is desirable to add 60-90wt.% of silica zeolite to the polyorganosiloxane membrane in usual and, by adding silica zeolite in this ratio, the PO₂ content of the polyorganosiloxane can be enhanced to several-ten several times as compared with that before silica zeolite is added. The thickness of the high silica zeolite-containing polyorganosiloxane membrane is usually 5-30 μm . This oxygen enriching membrane is excellent in oxygen permeability and oxygen separating capacity.